PRODUCT DATASHEET
Decor Corolle Wall G9 Black

Decor Corolle | Decorative luminaires made of colorful metal and glass with exchangeable light source



Areas of application

- Indoor applications
- Corridors, entrance areas, stairwells, living rooms, basements
- Bedrooms

Product benefits

- Allows to create a stylish retro style at home
- Different types of luminaires with the same design language maintain a consistent style at home
- High flexibility in the choice of the light source
- Sustainable solution thanks to exchangeable light sources
- Color matching textile cables

Product features

- Housing material: metal and glass
- Textile cable

503 Service Temporarily Unavailable

nginx


TECHNICAL DATA

Electrical data

Nominal voltage	220…240 V
Mains frequency	50…60 Hz
Protection class	I
Operating mode	Mains voltage

Dimensions & Weight

Length	135.00 mm
Width	210.00 mm
Height	245.00 mm
Product weight	620.00 g



DECOR COROLLE WALL G9

Materials & Colors

Product color	Black
Housing color	Black
Body material	Steel|glass
Glow Wire Test according to IEC 60695-2-12	650 °C

Application & Mounting

Ambient temperature range	-20…+40 °C
Temperature range at storage	-20…+80 °C
Type of connection	Terminal, 3-Pole (L, N, PE)
Type of protection	IP20/IP20
Protection class IK (shock resistance)	IK03
Dimmable	No
Mounting type	Surface
Mounting location	Wall

© 2026, LEDVANCE GmbH. All rights reserved.

Application environment	Indoor
With light source	No
Replaceable light source	No
Holder designation	G9

Emergency lighting

Type of emergency operation test	None

Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No

Additional product data

Number of illuminants	1

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- The external flexible cable or cord of this luminaire cannot be replaced; if the cord is damaged, the luminaire must be disposed of.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.
- Check wall-ceiling for suitability. If uncertain, seek professional advice.

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	User instruction / safety instructions	Decor Corolle Wall E27
PDF	Declarations of conformity	DECOR LUM

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854653889	Folding box 1	147 mm x 257 mm x 227 mm	1002.00 g	8.58 dm^3
4099854653896	Shipping box 4	530 mm x 310 mm x 249 mm	4618.00 g	40.91 dm^3

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

503 Service Temporarily Unavailable

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

503 Service Temporarily Unavailable