PRODUCT DATASHEET
Decor Corolle Pendant E27 Orange

Decor Corolle | Decorative luminaires made of colorful metal and glass with exchangeable light source



Areas of application

- Indoor applications
- Corridors, entrance areas, stairwells, living rooms, basements
- Bedrooms

Product benefits

- Allows to create a stylish retro style at home
- Different types of luminaires with the same design language maintain a consistent style at home
- High flexibility in the choice of the light source
- Sustainable solution thanks to exchangeable light sources
- Color matching textile cables

Product features

- Housing material: metal and glass
- Textile cable

© 2026, LEDVANCE GmbH. All rights reserved.

TECHNICAL DATA

Electrical data


Nominal voltage	220…240 V
Mains frequency	50…60 Hz
Protection class	I
Operating mode	Mains voltage

Photometrical data

Color rendering index Ra	> 80

Dimensions & Weight

Diameter	200.00 mm
Height	1215.00 mm
Product weight	900.00 g



DECOR COROLLE PENDANT E27

Materials & Colors

Product color	Orange
Housing color	Orange
Body material	Steel|glass
Glow Wire Test according to IEC 60695-2-12	650 °C

Application & Mounting

Ambient temperature range	-20…+40 °C
Temperature range at storage	-20…+80 °C
Type of connection	Terminal, 3-Pole (L, N, PE)
Type of protection	IP20/IP20
Dimmable	No
Mounting type	Suspended

© 2026, LEDVANCE GmbH. All rights reserved.

Mounting location	Ceiling
Application environment	Indoor
With light source	No
Replaceable light source	No

Emergency lighting

Type of emergency operation test	None

Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No

Additional product data

Number of illuminants	1

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- The external flexible cable or cord of this luminaire cannot be replaced; if the cord is damaged, the luminaire must be disposed of.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.
- Check wall-ceiling for suitability. If uncertain, seek professional advice.

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	User instruction / safety instructions	Decor Corolle Pendant E27
PDF	Declarations of conformity	DECOR LUM

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854654640	Folding box 1	222 mm x 222 mm x 257 mm	1312.00 g	12.67 dm^3
4099854654657	Shipping box 4	460 mm x 460 mm x 279 mm	6073.00 g	59.04 dm^3

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

© 2026, LEDVANCE GmbH. All rights reserved.

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

503 Service Temporarily Unavailable